

NDT Consultants Limited
Siskin Drive, Middlemarch House
CV3 4FJ Coventry, UK
Phone: +44(0)2476.511.151
Fax: +44(0)2476.511.696
WEB: www.ndt-consultants.co.uk
E-MAIL: sales@ndt-consultants.co.uk



TECHNICAL DATA SHEET

Ref: D 100

Page: 1/1

Rev: 1 Date: 05/05



MANUFACTURER : SHERWIN (USA)/NDT Europa (NL)
DISTRIBUTOR: NDT Consultants Limited (UK)

DESCRIPTION / APPLICATIONS:

Non aqueous wet, giving enhanced sensitivity for locating tight, incipient flaws.
Companion product(s): any type of penetrant (fluorescent or colored) used at ambient temperature.

SPECIFICATIONS / STANDARDS:

Complies with: ASME code and: ISO 3452-2 form d standard
specifications: **AMS 2644**

EADS all processes.

Approved: **PMUC** (Produits et Matériels Utilisables en Centrales, i.e. Products and Materials that can be Used in Nuclear Plants)

PACKAGING / SHIPPING / STORAGE:

Packaging: 1-, 5-, 10-liter canisters.

60-liter drum.

200-liter drum.

300-mL spray can.

Shipping / Handling: refer to MSDS.

Storage / Shelf life: keep away from moisture

Temperature limit : 0 to 50° C. (32°F to 120°F)

Keep packaging closed after taking out some of the product .

Canister / Barrel: > 48 months.

Spray can: > 48 months.

PHYSICO-CHEMICAL PROPERTIES:

Aspect: white powder in suspension in an organic medium.

Flash point: 12° C. (24°F)

Very low halogen and sulfur content

Compatible with all metals, ceramics and certain synthetic materials.

HEALTH AND SAFETY: refer to MSDS.

The information given herein is given in good faith to our customers for the sole purpose of assisting them in the use of the products. The document contains no formal or implicit guarantee regarding its use. NDT Consultants Limited cannot be held responsible for damages of any nature resulting from information provided in this document. In addition, none of the information which the document contains should be interpreted as a recommendation for the use of the products which would infringe the protected rights of industrial property.